

TECHNICAL DATA



GLASS CLOTH TAPE

**Product Code: 1G08S
(Flame Retardant)**

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : <http://www.pleo.com>



UL FILE #E126174

Description : 1G08S is a Glass Cloth Tape with silicone adhesive. It is designed to offer efficiencies in application and versatility in selection.

Application : Coil wrap, crossover insulation, coil banding.

Features/Benefits : Resistance to flapping and varnish solvents. Razor slitting is used to provide fray-free edges. 1G08S also complies with UL510 flame retardant requirements.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	TOTAL THICKNESS	mm	0.215 ± 0.02
	TENSILE STRENGTH	kg/25mm	47.5
	ELONGATION	%	5
	ADHESION TO STEEL	kg/25mm	0.6
	DIELECTRIC BREAKDOWN	kV	3
	TEMPERATURE RATING	°C	180

Color : White

Availability : Standard 55M roll, 3" core, width 1080mm

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

