



## E-Core and Lamination Size Cross Reference

Visit [www.lodestonepacific.com](http://www.lodestonepacific.com) to see our extensive list of over 500 Bobbins in a wide variety of configurations, sizes, and materials



sales@lodestonepacific.com  
www.lodestonepacific.com  
Phone: (714) 970-0900

US Lam Size (1)	Metric Lam Size (2)	US E Cores Size (1)	Metric E Cores Size (2)	Back Length Inch (3)	Back Length mm (3)	Leg Length Inch (3)	Leg Length mm	Window Width Inch (3)	Window Width mm (3)	Thick Inch (4)	Thick mm (4)
EI-14				0.55	14.0	0.276	7.0	0.14	3.5	(4)	(4)
	EF16	E16/8/5		0.63	16.0	.228	5.8	0.19	4.7	0.19	4.7
EI-18				0.75	19.0	0.437	11.0	0.19	4.7	(4)	(4)
EI-19				0.75	19.0	0.394	10.0	0.20	5.0	(4)	(4)
	EI187			0.75	19.0	0.455	11.6	0.19	4.7	0.187	4.7
		E-19/8/5		0.75	19.0	0.433	11.0	0.19	4.8	0.189	4.8
	EF20	E20/10/6		0.75	20.9	.276	7.0	0.23	5.9	0.23	5.9
EI-24				0.94	24.0	0.472	12.0	0.24	6.0	(4)	(4)
		E-25/10/7		1.00	25.4	0.488	12.4	0.26	6.5	0.256	6.5
	EE2425			1.00	25.4	0.500	12.7	0.25	6.4	0.250	6.4
EI-25				1.00	25.4	0.500	12.7	0.25	6.4	(4)	(4)
	EF25	E25/13/7		1.00	25.0	0.500	12.8	0.25	7.5	0.295	7.5
EI-28				1.10	28.0	0.669	17.0	0.31	8.0	(4)	(4)
		E30/15/7		1.18	30.0	0.764	19.4	0.28	7.0	0.276	7.0
EI-30				1.18	30.0	0.591	15.0	0.39	10.0	(4)	(4)
	EF32	E32/16/9		1.26	32.0	0.646	16.4	0.37	9.5	0.374	9.5
E-I33				1.30	33.0	0.669	17.0	0.39	10.0	(4)	(4)
EI-31				1.38	35.0	0.781	20.0	0.31	8.0	(4)	(4)
		E-35/14/9		1.36	34.5	0.374	9.5	0.37	9.3	0.366	9.3
	EI375			1.38	34.9	0.770	19.6	0.38	9.5	0.375	9.5
EI-37 (EI375)				1.38	35.0	0.750	19.0	0.38	9.5	0.374	9.5
EI-35				1.38	35.0	0.768	19.5	0.38	9.6	(4)	(4)
		E35/18/10		1.38	35.0	0.492	12.5	0.39	10.0	0.394	10
EI-36				1.42	36.0	0.709	18.0	0.47	12.0	(4)	(4)
EI-38				1.50	38.0	0.756	19.2	0.50	12.8	(4)	(4)
	EI21	E-41/17/12		1.61	41.0	0.650	16.5	0.49	12.5	0.488	12.4
EI-41				1.61	41.0	0.827	21.0	0.51	13.0	(4)	(4)
EI-50				1.63	41.2	0.813	20.6	0.50	12.7	(4)	(4)
EI-42				1.65	42.0	0.827	21.0	0.55	14.0	(4)	(4)
		E-43/21/11		1.69	43.0	0.827	21.0	0.47	12.0	0.433	11.0
		E-42/21/15		1.69	43.0	0.827	21.0	0.48	12.2	0.591	15.0
	EE42x20	E-42/21/20		1.69	43.0	1.181	30.0	0.48	12.2	0.787	20.0
		E47/20/16		1.85	47.0	0.787	20.0	0.61	15.6	0.614	15.6
	EI625			1.87	47.4	0.952	24.2	0.62	15.7	0.620	15.7
EI-62				1.88	47.6	0.938	23.8	0.63	15.9	(4)	(4)
EI-48				1.89	48.0	0.945	24.0	0.63	16.0	(4)	(4)
EI-68				2.06	52.4	1.031	26.2	0.69	17.5	(4)	(4)
EI-54				2.13	54.0	1.063	27.0	0.71	18.0	(4)	(4)
		E-55/28/21		2.17	55.0	1.094	27.8	0.67	17.0	0.827	21.0
		E-55/28/25		2.17	55.0	1.094	27.8	0.68	17.2	0.984	25.0
		E-56/24/19		2.20	56.0	0.929	23.6	0.78	19.8	0.740	18.8
	E-75			2.24	56.9	1.140	29.0	0.75	18.9	0.745	18.9
EI-57				2.24	57.0	1.122	28.5	0.75	19.0	(4)	(4)



**Notes:**

- (1) Characterized by Center Leg Width in Inches
- (2) Characterized by Back Leg Length in mm.
- (3) Tolerances vary between Manufacturers
- (4) Stack Thickness is User Controlled





## E-Core and Lamination Size Cross Reference

Visit [www.lodestonepacific.com](http://www.lodestonepacific.com) to see our extensive list of over 500 Bobbins in a wide variety of configurations, sizes, and materials

sales@lodestonepacific.com  
[www.lodestonepacific.com](http://www.lodestonepacific.com)  
 Phone: (714) 970-0900

US Lam Size (1)	Metric Lam Size (2)	US E Cores Size (1)	Metric E Cores Size (2)	Back Length Inch (3)	Back Length mm (3)	Leg Length Inch (3)	Leg Length mm	Window Width Inch (3)	Window Width mm (3)	Thick Inch (4)	Thick mm (4)
EI-87				2.63	66.7	1.313	33.3	0.88	22.2	(4)	(4)
EI-68				2.68	68.0	1.339	34.0	0.87	22.0	(4)	(4)
		E-71/33/32		2.80	71.0	1.307	33.2	0.87	22.0	1.260	32.0
		E-72/28/19		2.83	72.0	1.402	35.6	0.75	19.0	0.748	19.0
EI-75				2.24	57.0	1.125	28.6	0.75	19.0	(4)	(4)
EI-75				2.95	75.00	1.476	37.5	0.91	23.0	(4)	(4)
EI-93				3.00	76.2	1.563	39.7	0.94	23.8	(4)	(4)
EI-100				3.00	76.2	1.500	38.1	1.00	25.4	(4)	(4)
EI-78				3.07	78.0	1.535	39.0	1.02	26.0	(4)	(4)
		E-80/38/20		3.15	80.0	1.516	38.5	0.79	20.0	0.787	20.0
EI-84				3.31	84.0	1.654	42.0	1.10	28.0	(4)	(4)
EI-112				3.38	85.7	1.688	42.9	1.13	28.6	(4)	(4)
EI-90				3.54	90.0	1.772	45.0	1.18	30.0	(4)	(4)
EI-125				3.75	95.3	1.875	47.6	1.25	31.8	(4)	(4)
		E-96/42/26		3.78	96.0	1.969	50.0	1.24	31.6	1.00	25.5
EI-96				3.78	96.0	1.890	48.0	1.26	32.0	(4)	(4)
		E100/60/28		3.94	100.0	1.843	46.8	1.08	27.5	1.08	27.5
EI-137				4.13	104.8	1.063	27.0	1.38	34.9	(4)	(4)
EI-105				4.13	105.0	2.067	52.5	1.38	35.0	(4)	(4)
EI-108				4.25	108.0	2.126	54.0	1.42	36.0	(4)	(4)
EI-150				4.50	114.3	2.250	57.2	1.50	38.1	(4)	(4)
		E-114/46/35		4.49	114.0	2.756	70.0	1.38	35.0	1.378	35.0
EI-120				4.72	120.0	2.362	60.0	1.57	40.0	(4)	(4)
		E-120/52/32		4.72	120.0	2.480	63.0	1.57	40.0	1.260	32.0
EI-126				4.96	126.0	2.480	63.0	1.65	42.0	(4)	(4)
EI-175				5.25	133.4	2.625	66.7	1.75	44.5	(4)	(4)
EI-135				5.31	135.0	2.657	67.5	1.77	45.0	(4)	(4)
EI-162				5.75	146.1	2.625	66.7	1.63	41.3	(4)	(4)
EI-150				5.91	150.0	2.953	75.0	1.97	50.0	(4)	(4)
EI-212				6.38	161.9	3.188	81.0	2.13	54.0	(4)	(4)
EI-225				6.75	171.5	3.375	85.7	2.25	57.2	(4)	(4)
EI225 S				7.06	179.4	3.531	89.7	2.25	57.2	(4)	(4)
EI-180				7.09	180.0	3.543	90.0	2.36	60.0	(4)	(4)
EI-200				7.50	190.5	3.750	95.3	2.00	50.8	(4)	(4)
EI-250				7.50	190.5	3.750	95.3	2.50	63.5	(4)	(4)
EI192				7.56	192.0	5.039	128.0	2.52	64.0	(4)	(4)
EI-300				9.00	228.6	4.500	114.3	3.00	76.2	(4)	(4)
EI240				9.45	240.0	4.724	120.0	3.15	80.0	(4)	(4)
EI250				9.84	250.0	4.921	125.0	3.15	80.0	(4)	(4)
EI300				11.81	300.0	5.906	150.0	3.94	100.0	(4)	(4)
EI-400				12.00	304.8	6.000	152.4	4.00	101.6	(4)	(4)
EI-500				15.00	381.0	7.500	190.5	5.00	127.0	(4)	(4)



**Notes:**

- (1) Characterized by Center Leg Width in Inches
- (2) Characterized by Back Leg Length in mm.
- (3) Tolerances vary between Manufacturers
- (4) Stack Thickness is User Controlled

